



Specifications:

- Material: Polyester, UL 94V-0
- Voltage Rating: 250V
- Current Rating: 5A
- Withstand Voltage: 1500V AC/Minute
- Insulation Resistance: 1000M Ω min.
- Temperature Range: -25°C~+85°C
- Contact Resistance: Initial value/10m Ω max.
After environmental testing/20m Ω max.
- Standard Color: Black

Dimensional & Ordering Information:

Circuits	Part No	Dimensions mm	
		A	B
02	CMF-H300M-2x01		4.0
04	CMF-H300M-2x02	3.00	7.0
06	CMF-H300M-2x03	6.00	10.0
08	CMF-H300M-2x04	9.00	13.0
10	CMF-H300M-2x05	12.00	16.0
12	CMF-H300M-2x06	15.00	19.0
14	CMF-H300M-2x07	18.00	22.0
16	CMF-H300M-2x08	21.00	25.2
18	CMF-H300M-2x09	24.00	28.2
20	CMF-H300M-2x10	27.00	31.2
22	CMF-H300M-2x11	30.00	34.2
24	CMF-H300M-2x12	33.00	37.2

所有材料為
"環保材料"
2009.6.06
RoHS



DESCRIPTION(內容): 3.0mm (.118") Micro-Fit connector PART NO: (料號) CMF-H300M-2xXX DWG NO(圖號): 5750-H	DRAWN(製圖): GONG	GENERAL TOLERANCE: (公差) .000 ±0.08 .00 ±0.13 .0 ±0.25	REV: R1	REV	DESCRIPTION	DATE	
	CHECKED(確認): MANDY		UNIT: mm	R0		RELEASE	2009.06.06
	APPROVAL(核准): JOHNNY	SCALE(比例): FREE	SIZE: A4	R1		2014年8月料號P數編碼統一兩碼	2015.01.21
			SHEET: 1/1	R2			
			R3				