



MATERIAL:

Insulator: NYLON66 UL94V-0+GF Black
 Contact: Brass Gold 2u" over nickel plated

NOTES:

- 1.ASSEMBLY TOTAL LENGTH 57.0±2.0
- 2.WATERPROOF RATE:IP68
- 3.UV RESIST

ORDERING CODE

LJ125 XXX AS - PF XX D 08

SERIES ————
 PIN OPTION ————
 210=2+5P (7A+3A AC.DC)
 180=2~3P (10A AC.DC)
 100=4~6P (5A AC.DC)
 075=10~18P (2A AC.DC)

ASSEMBLY TYPE ————

Cable ID OPTION
 08=Ø8mm, 10=Ø10mm

D=W/DUST COVER
 N=W/O DUST COVER

NO. OF CONTACTS
 RM=MALE PIN
 PF=FEMALE PIN

| CIRCUITS | 2P | 3P | 4P | 5P | 6P | 2+5P | 18P |
|------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| ARRANGEMENT OF CONTACT | | | | | | | |
| SERIES | LJ125180-02 | LJ125180-03 | LJ125100-04 | LJ125100-05 | LJ125100-06 | LJ125210-07 | LJ125075-18 |

| | | | | | | | | | |
|---|----------|---|------------------|---------|-----|------|------------|------|----|
| 詮盛企業股份有限公司 CHIEN SHERN ENTERPRISE CO.,LTD. | TITLE | QUICK PULL IN-OUT WATER PROOF CONNECTOR FEMALE PIN ASS'Y | TOLERANCE | DRAWN | 許建華 | DATE | 2011.05.25 | | |
| | PART NO. | LJ125XXXAS-PFXXD08 | DIM. .0 ±0.30 | CHECK | | DATE | | | |
| | DWG.NO. | LJ125XXXAS-PFXXD08 | .00 ±0.20 | APPROVE | | DATE | | | |
| | | | .000 ±0.10 | SCALE | | UNIT | mm | REV. | 01 |