



P.C.B. LAYOUT

MATERIAL

- * Contact material: Phosphor bronze
- * Contact plating: 150u Tin over 40u" nickel
- * Insulator: HI-temp pps nature UL94V-0

SPECIFICATIONS

- * Temperature range: -50°C~+105°C
- * Current rating: 1A
- * Capacitance: 1.0 Picaforads(Max)
- * Contact resistance: 30 Milliohms (Max)
- * Insulation resistance: 1,000 Megohms (Max)
- * Withstanding voltage: 600V AC/minute

CIRCUITS	DIMENSION(mm)			
	A	B	C	D
20	15.68	15.68	5.08	5.08
28	18.22	18.22	7.62	7.62
32	20.76	20.76	10.16	10.16
44	23.30	23.30	12.70	12.70
52	25.84	25.84	15.24	15.24
68	30.92	30.92	20.32	20.32
84	36.00	36.00	25.40	25.40

詮盛企業股份有限公司

CHIEN SHERN ENTERPRISE CO., LTD.

TITLE	1.27mm pitch SURFACE MOUNT PLCC SOCKET		GENERAL TOLERANCE	DRAWN		DATE	94/11/02		
	PART NO.	PLCC-S-XX	DIM: X. ±0.5 X.X ±0.25 X.XX ±0.2 X.XXX ±0.08	CHECK		DATE			
				APPROVE		DATE			
	DWG.NO.	PLCC-S-XX		SCALE	2:1	UNIT	mm	REV.	01