



RECOMMEND P.C.B. LAYOUT
TOP VIEW

NOTES

***Material:**

- 1.Body: PPS UL 94V-0 Rated, Color:Black;
- 2.Cover: PPS UL 94V-0 Rated, Color:Black;
- 3.Contact: Phosphor Bronze;
- 4.Contact Plating: Gold Plating Over Nickel on Contact Area, Tin/Lead Plating on Terminal.

***Specification:**

- 1.Current Rating: 0.5 AMP. Max.;
- 2.Dielectric Withstanding Voltage: 500V AC R.M.S For One Minute;
- 3.Insulation Resistance: 1000 M Ohms Min. AT 500V AC;
- 4.Contact Resistance: 30 M Ohms Max.;
- 5.Operating Temperature: -25°C to +85°C;
- 6.Processing Temp: 260°C for 30~60 Seconds Max.;

ORDER INFORMATION

SIM40-08 SA 1 R
1 2 3 4 5

1. SERIES NO
2. NO. OF POS
3. CONTACT PLATED OPTION
GOLD PLATING ON CONTACT
AREA TIN PLATING ON SOLDER AREA
SA=GOLD FLASH
SB=GOLD 5u"
SC=GOLD 10u"
SD=GOLD 15u"
SE=GOLD 30u"
4. POST OPTION
0=W/O LOCATING PEG
1=W/LOCATING PEG
5. PACKING
R=TAPE&REEL

詮盛企業股份有限公司

CHIEN SHERN ENTERPRISE CO.,LTD.

TITLE	SIM CARD CONN WITH COVER	GENERAL TOLERANCE	DRAWN	許建華	DATE	2005.11.02		
PART NO.	SIM40-08SA1R	DIM: X. ±0.5 X.X ±0.25 X.XX ±0.2 X.XXX ±0.08	CHECK		DATE			
DWG.NO.	SIM40-08SA1R		APPROVE		DATE			
			SCALE	1:1	UNIT	mm	REV.	01