



Test Equipment:			Humidity	70%	Temperature:	21°C
ID	Product Number		Description		Manufacturer	
1	TDS8200+80E04		TDR with TDR and TDT module		Tektronix	
2	N5230A 300k~20GHz		ENA		Agilent	
Device Under Test(DUT) Information:						
Vendor		ICT	Customer:			
Part number:		TF-1R21-0052	Date:		8-Aug-08	
DUT Description:		SATA Receptacle Gen 2.5 Test Fixture				

Test Report

Mated Connector Impedance @70ps Rise time filter (20-80%)

Conn no.	Pair Num	Result	Spec Max	Spec Min	Max value	Min Value	△Value	Unit	Image
SMA	1	Pass	105	95	101.65	100.64	1.01	Ohms	Click here
	2	Pass	105	95	103.03	100.39	2.64	Ohms	
SATA	1	Pass	108	92	105.96	97.35	8.61	Ohms	Click here
	2	Pass	108	92	105.61	96.64	8.97	Ohms	

Intra Pair Skew

Conn no.	Pair Num	Result	Spec Max	Value	Unit	Image
P1	1	Pass	2	0.2	ps	Click here
	2	Pass	2	0.6	ps	

Cross talk

Conn no.	Frequency	Result	Spec Max	Value	Unit	Image
P1	10M~6G	Pass	-36	-43.82	dB	Click here

Insertion Loss (-3dB)

Conn no.	Pair Num	Result	Spec Min	Value	Unit	Image
P1	1	Pass	7.5G	8.1G	Hz	Click here
	2	Pass	7.5G	8.4G	Hz	

Note: a. Pair Num is from Connector P1 unless specified.

Approved:

Checked: Steven

Tested: Alan

Mated Connector Impedance

Pair 1 Waveform



[Click here to Go back](#)

Pair 2 Waveform



Intra Pair Skew

Pair 1 Waveform


P1-12

[Click here to go back](#)



此數值除以2為Skew

P1-34




此數值除以2為Skew

Cross talk

[Click here to go back](#)

Pair 1 Waveform



Insertion Loss

[Click here to Go back](#)

Pair 1 Waveform



Pair 2 Waveform

