



SPECIFICATIONS:

- Current Rating : 1A
- Dielectric withstanding Voltage : 1000v RMS/minute
- Insulator resistance : 5000 Megohms min.
- Contact resistance : 20 milliohms initial
30 milliohms after test.
- Operating temperatures : -25°c to 85°c
- Insertion force : 340g max.per contact.
- Withdrawal force : 80g min.per contact

Material:

- contact:
phosphor Bronze thickness 0.15mm
- Contact Plating, Tin plated
- Insulator: PBT , UL 94V-0

CKT	A±0.20	B±0.20	C±0.20	D±0.20	Space	CKT	A±0.20	B±0.20	C±0.20	D±0.20	Space
6	7.62	5.08	10.16	7.62	03	24	30.48	27.94	17.78	15.24	06
8	10.16	7.62	10.16	7.62		28	35.56	33.02	17.78	15.24	
14	17.78	15.24	10.16	7.62		32	40.64	38.10	17.78	15.24	
16	20.32	17.78	10.16	7.62		40	50.80	48.26	17.78	15.24	
18	22.86	20.32	10.16	7.62		42	53.34	50.80	17.78	15.24	
20	25.40	22.86	10.16	7.62		48	60.96	58.42	17.78	15.24	
24	30.48	27.94	10.16	7.62							
28	35.56	33.02	10.16	7.62							

<p>JAWS 兆旭股份有限公司 JAWS CO., LTD. 7F-1, NO.31, Lane 169, Kang Ning Street, Hsichih, Taipei Hsien, Taiwan. TEL:886-2-2692-2898 FAX:886-2-2692-2618 Http://www.jaws.com.tw</p>	<p>THIRD ANGLE PROJECTION</p>	<p>DESIGN UNITS ■ mm □ INCH</p>	<p>TITLE: 2.54mm SHRINK IC SOCKET</p>	<p>GENERAL TOLERANCES: ±0.30</p>		<p>DRAWN 游熾瑩</p>	<p>DATE 96/10/26</p>
	<p>SIZE: A4</p>	<p>SCALE: FREE</p>	<p>SHEET: 1/1</p>	<p>PARTS NO.: 254M-xxP-x</p>		<p>CHECK </p>	<p>DATE 96/10/26</p>
	<p>CPN NO.:</p>	<p>DWG NO.: JAWS-SOP-254M001</p>		<p>REV. 04</p>		<p>APPROVE </p>	<p>DATE 96.10.30</p>
	<p>DAN NO.: P9610-060</p>						