


RECOMMENDED PCB LAYOUT



FPC/FFCT=0.30±0.05

MATERIAL

INSULATOR: GLASS-REINFORCED THERMOPLASTIC.
CONTACT: COPPER ALLOY.
PLATING: TIN/LEAD PLATED OVER NICKEL

ELECTRICAL

CURRENT RATING: 0.5 AMP.
DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC MIN.
INSULATION RESISTANCE: 1000 MEGAOHMS MIN.
CONTACT RESISTANCE: 30 MILLIOHMS MAX.

ENVIRONMENTAL

TEMPERATURE RANGE: -40°C TO +85°C.

DIMENSION TABLE

Circuits	Dimension			Circuits	Dimension		
	A	B	C		A	B	C
3	2.00	4.1	6	20	19.00	21.1	23
4	3.00	5.1	7	21	20.00	22.1	24
5	4.00	6.1	8	22	21.00	23.1	25
6	5.00	7.1	9	23	22.00	24.1	26
7	6.00	8.1	10	24	23.00	25.1	27
8	7.00	9.1	11	25	24.00	26.1	28
9	8.00	10.1	12	26	25.00	27.1	29
10	9.00	11.1	13	27	26.00	28.1	30
11	10.00	12.1	14	28	27.00	29.1	31
12	11.00	13.1	15	29	28.00	30.1	32
13	12.00	14.1	16	30	29.00	31.1	33
14	13.00	15.1	17	31	30.00	32.1	34
15	14.00	16.1	18	32	31.00	33.1	35
16	15.00	17.1	19	33	32.00	34.1	36
17	16.00	18.1	20	34	33.00	35.1	37
18	17.00	19.1	21	35	34.00	36.1	38
19	18.00	20.1	22	36	35.00	37.1	39