



**Features**

Double tuning fork type contact guarantees high reliability  
 2.54mm pitch low-profile mini type match to 0.64mm SQ. posts

**Material**

Insulator : PBT, UL 94V-0  
 Contact : See order information  
 Terminal : Brass / Phosphor Bronze  
 Packing : Bag

**Specification**

Current Rating : 3 Amperes max.  
 Contact Resistance : 30 mΩ max.  
 Insulation Resistance : 1000 MΩ min.  
 Dielectric Withstanding Voltage : AC 650 Volts RMS.

No. of contacts per row (02-13P)  
 Ex. 2x5 : 05

**Plating code**

GF : 0.6μ" Gold plated on contact area (standard)  
 G3 : 10μ" Gold plated on contact area  
       0.6μ" Gold plated on the other  
 G4 : 15μ" Gold plated on contact area  
       0.6μ" Gold plated on the other  
 G5 : 30μ" Gold plated on contact area  
       0.6μ" Gold plated on the other  
 TA : 80μ" Tin plated on contact area  
 TB : 200μ" Tin plated on contact area

MJ1PBxxxxx1

**Base Color**

A : Black (standard)  
 C : Red  
 E : Yellow  
 F : Green  
 G : Blue  
 J : White

**Material**

A : PBT + Brass (standard)  
 B : PBT + Phosphor Bronze

**JAWS** 兆旭股份有限公司  
 JAWS CO., LTD.

7F., No.31, Ln. 169, Kangning St., Xizhi Dist.,  
 New Taipei City 221, Taiwan (R.O.C.)  
 TEL:886-2-2692-2898  
 FAX:886-2-2692-2618  
 Http://www.jaws.com.tw



SIZE: A4	SCALE: FREE	SHEET: 1/1
CPN :	DAN NO.: S10009-012	

DESIGN UNITS  
 ■ mm □ INCH

TITLE: 2.54mm Parallel Jumper  
 Open Type (Base : 6mm)

PARTS NO.: MJ1PBxxxxx1

DWG NO.: JAWS-SOP-MJ009

GENERAL TOLERANCES:

±0.30

DRAWN	游熾瑩	DATE	2011/09/28
CHECKED	Wang	DATE	2011/09/28
APPROVED	Wes	DATE	2011/09/28