



Rated Current	Breaking capacity	Rated Voltage
100mA	10KA/125V/AC 35A/250V/AC	125V/250V
125mA		125V/250V
160mA		125V/250V
200mA		125V/250V
250mA		125V/250V
300mA		125V/250V
315mA		125V/250V
400mA		125V/250V
500mA		125V/250V
600mA		125V/250V
630mA	125V/250V	
700mA	125V/250V	
800mA	125V/250V	
1A	125V/250V	
1.25A	10KA/125V/AC 100A/250V/AC	125V/250V
1.5A		125V/250V
1.6A		125V/250V
2A		125V/250V
2.5A		125V/250V
3A		125V/250V
3.15A	125V/250V	
3.5A	125V/250V	
4A	10KA/125V/AC 200A/250V/AC	125V/250V
5A		125V/250V
6A		125V/250V
6.3A		125V/250V
7A		125V/250V
7.5A		125V/250V
8A		125V/250V
9A		125V/250V
10A		125V/250V
12A		1000A/32V/AC 100A/125V/AC 200A/250V/AC
13A		
15A		
16A		
20A		
25A		
30A		

Characteristic specification according to UL 248-1, 14

◎Clear-Time-Current Characteristics

% of Amp rating	100%	135%	200%
Opening Time	Min.	Max.	Max.
Rated Current	4 h	3600 S	120 S

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN mm
TOLERANCE
DECIMALS ANGULAR
X ± 0.5 ± 2°
XX ± 0.25
DO NOT SCALE DRAWING

P/N

REV B

CUSTOMER NO.

DRAWN BY Belliel

CHECKED BY 林進有

APPROVED BY 楊肇元

DATE 2020.07.23

SCALE

JENN FENG ELECTRIC INDUSTRIAL CO., LTD

TITLE

Miniature Cartridge Fuse 6.35X22.2mm

PART NO. MFG22

DRAWING NO. AA06092902