



CONNECTOR SPECIFICATIONS

MATERIAL

- PIN:BRASS
- PIN PLATING:GOLD
- DIELECTRIC:P.P
- BODY:BRASS
- BODY PLATING:NICKEL

ELECTRO-MECHANICAL

- 500 MINIMUM MATING CYCLES
- 50 OHM IMPEDANCE
- 5000 MEGOHM MINIMUM INSULATION RESISTANCE AT 500VDC
- 500V PEAK VOLTAGE RATING
- 1500V RMS DIELECTRIC WITHSTANDING VOLTAGE
- TEMPERATURE RANGE:-55°C TO +155°C
- VIBRATION,SHOCK&TEMPERATURE CYCLING
- IN ACCORDANCE WITH MIL-STD-1344
- INTERFACE DIMENSIONS SIMILAR TO MIL-C-39013

 <b>易昕企業有限公司</b> LEAMAX ENTERPRISE CO., LTD.			
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO <b>3288</b>
APP			MODEL
CHK	CCJ	92.11.13	FILE NO BNC MALE TO RCA FEMALE
DGN	AMY	92.11.13	REV. X1
DRW	SHIEH	92.11.13	UNIT MM
			SHT 1 OF 1
			SIZE A4