

NOTES:

ELECTRICAL:

- 1.VOLTAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :1.5 AMP
- 3.CONTACT RESISTANCE :30 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE :1000 MEGOHMS MIN @ 500 VDC
- 5.DIELECTRIC STRENGTH :1000 VAC RMS 60Hz,1 MIN



MECHANICAL:

- 1.HOUSING MATERIAL :GLASS FILLED POLYESTER or HIGH TEM.UL94V-0
- 2.CONTACT MATERIAL :PHOSPHOR BRONZE t:=0.35mm
- 3.PLATING : 1:CONTACT AREA-SELECTIVE GOLD PLATING
2:TAILS-150u" TIN-LEAD MIN OVER 50u"NICKEL
- 4.OPERATING LIFE :750 CYCLES MIN
- 5.PCB RETENTION PRE-SOLDER :1 LB MIN
- 6.PCB RETENTION POST-SOLDER :10 LBS MIN

ENVIRONMENTAL:

- 1.STORAGE : -40°C TO +85°C
- 2.OPERATION: 0°C TO 70°C

PCB LAYOUT (COMPONENT SIDE VIEW)

 易昕企業有限公司 LEAMAX ENTERPRISE CO., LTD.					
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 8724-SMT		
APP		92.01.30	MODEL	FILE NO	REV.
CHK	CCJ	90.11.01	TOP ENTRY SMT	RJ 6P/6C	X1
DGN	AMY	90.11.01	UNIT	SHT 1 OF 1	SIZE
DRW	SHIEH	90.11.01	MM		A4