



SPECIFICATIONS

MATERIAL:

- 1. Housing : PBT Polyester UL94V0
- 2. Color : Black
- 3. Contacts : 0.45mm Diameter Phos-Bronze Plated With Hard Gold
- 4. Shield : 0.20mm Thickness Copper Alloy With Tin/Nickel Plated

ELECTRICAL:

- 1. Current Rating : 1.5 AMP
- 2. Voltage Rating : 150 VAC
- 3. Contact Resistance : 20 Milliohms MAX
- 4. Insulation Resistance : 500 Milliohms MIN
- 5. Dielectric Withstanding Voltage : 1000 VAC, 1min

UL. CUL NO.: E166003

Ports	Dimensions m/m		
	A	B	C
1	13.10	9.70	12.90
2	26.70	23.10	26.50

.X ±0.3	UNITS mm	TITLE:	
		RJ11 6P Very L/P Shielded Modular Jack	
.XX ±0.20	SCALE Free	APPD: SHIEH	PART NO.: 87316P6C022AB06BK
		CHKD:	87316P6C022AB06AK
TOLERANCE		DR: AMY SHEN	
		SHEET: 1/1	易昕企業有限公司 LEAMAX ENTERPRISE CO., LTD
		REV: A	
		DATE: 06/24/03	