


Female	A±0.2	B±0.3	C±0.3	D±0.5	E±0.3	F±0.3	G±0.3	H±0.3
PH16-09S	2.95	9.85	6.85	1.35	13.10	22.40	11.20	19.50
PH16-15S	2.95	11.70	6.75	1.35	13.10	30.90	11.20	28.20
PH16-25S	2.90	13.50	6.55	1.30	13.10	44.35	11.15	41.65
PH16-37S	2.85	15.80	7.20	1.30	13.20	61.30	11.40	58.60
PH16-50S	2.90	11.90	8.00	1.50	13.80	54.70	10.80	51.70

Male	A±0.2	B±0.3	C±0.3	D±0.5	E±0.3	F±0.3	G±0.3	H±0.3
PH16-09P	2.95	9.85	6.90	1.50	14.60	24.00	12.60	21.30
PH16-15P	2.95	11.90	6.65	1.20	14.60	32.70	12.60	30.00
PH16-25P	2.95	13.80	6.70	1.40	14.70	46.20	12.70	43.40
PH16-37P	2.75	15.80	7.20	1.30	14.70	62.90	12.60	60.20
PH16-50P	2.90	12.00	8.10	1.50	14.90	57.10	11.90	54.10



NO.410, FU-TEH 1ST ROAD,  
SHIJR, TAIPEI COUNTY  
221, TAIWAN, R.O.C.

TEL: 886-2-26945824

FAX: 886-2-26946971

**TITLE**

**PARTS NO.**

**DWG. NO.**

D-SUB Connector  
Protect Shell

PH16-09~50P

**GENERAL TOLERANCE**

DIM:  
X. ±0.30  
X.X ±0.20  
X.XX±0.10

**DRAWN**

**CHECK**

**APPROVE**

**SCALE**

**DATE**

**DATE**

**DATE**

**UNIT**

93/07/04

103/03/19

MM REV. B