

ITEM	PW-5002	PW-5032
Power Transformer:	E.I. Type Transformer	E.I. Type Transformer
Max. Continual Output Power:	105VA	
Max. Raised Temperature:	< 40°C	< 40°C
Independent Output:	0~30V/0~3A, 5V Fixed / 0~3A; Dual Output	
Constant Voltage Characteristic		
Load Regulation:	$\pm 0.05\% + 2mV$	$\pm 0.01\% + 10mV$
Line Regulation:	$\pm 0.05\% + 2mV$	$\pm 0.01\% + 5mV$
Ripple & Noise:	< 0.4mVrms	< 0.4mVrms
Output Switch:	Built-in Output Switch(Master & Fixed 5V)	
Constant Current Characteristic		
Load Regulation:	< 15mA	
Line Regulation:	$\pm 0.05\% + 2mA$	$\pm 0.01\% + 2mA$
Ripple & Noise:	< 2.5mArms	< 2.5mArms
Current Limit Switch:	Built-in C.C. Limit Switch (Master)	
5V Fixed Output		
Regulation:	Line Regulation < 5mV, Load Regulation < 10mV	
Ripple & Noise:	< 1.5mVrms	< 1.5mVrms
Voltage Accuracy:	5V $\pm 0.25V$	
Max. Output Current:	3A	
Output Switch:	Built-in Output Switch	
Display		
Voltage:	3 Digits 0.56" Green LED	4 Digits 0.36" Green LED
Current:	3 Digits 0.56" Red LED	4 Digits 0.36" Red LED
Accuracy:	0.1% + 2 digits	0.05% + 3 digits
General		
Power Source:	ACV 115/230 $\pm 10\%$, 50/60Hz	
Dimensions(W x H x D):	230 x 170 x 310 mm	
Weight:	6.7 kg	6.8 kg