



Drawing Number: P4-011-□□□□□

1. Housing Material: Polycarbonate, UL Flammability Rating:

①=UL 94V-0, RoHS Compliant.

②=UL 94V-2, RoHS Compliant.

2. Contacts Type: ①=Straight pin fits Stranded wire only.

②=Two prong angled pin fits Solid/Stranded Wires.

③=Three prong pin fits Solid/Stranded Wires.

3. Gold Plating: Ⓣ= Fu" (Flash), ⓐ=2-3u" ($0.0508 \mu m \leq A \leq 0.0762 \mu m$),

ⓗ= 3u" ($\geq 0.0762 \mu m$), Ⓢ= 6u" ($\geq 0.1524 \mu m$),

Ⓤ=15u" ($\geq 0.381 \mu m$), Ⓦ=30u" ($\geq 0.762 \mu m$),

Ⓟ=50u" ($\geq 1.27 \mu m$).

4. Packaging Quantity: Ⓢ=1000pcs, Ⓣ=500pcs, Ⓤ=250pcs, Ⓦ=200pcs

Ⓧ= 100pcs, Ⓨ= 50pcs, Ⓩ= 25pcs, ⓐ= 10pcs

ⓑ= Other

5. Housing Color: Transparent, other colors are available.

(Red=RD, Orange=OR, Yellow=YL, Green=GN, Blue=BL, Purple=PU, Black=BK)

6. Shielded Material: Brass with nickel plated, or Non-Shielded.

7. Operating Temperature: -10°C to 60°C.

NO: PX-0XX-□□□□□

- Housing Material (0, 2)
- Contacts type (1, 2, 3)
- Gold plating (F, A, H, B, C, D, E)
- Packaging Quantity (S, T, U, V, W, X, Y, Z)
- Housing Color (RD, OR, YL, GN, BL, PU, BK)



□ Straight pin



□ Two prongs pin



□ Three prongs pin

NOTE TOL: ±0.1

B	2017.09.27. Rescheduling coding	3RD	⊕	Drawing	Chidy	Date	2011/03/20
A	An initial version	Unit	m/m	Checked	Chris	Date	2011/03/20
Rev	Description	Scale	1:1	Approved	Jason	Date	2011/03/20

UL Code	4P4C-S
Description	
F-Shielded with two latches	



Plug Master
INDUSTRIAL CO., LTD
www.plugmaster.com.tw