

.050"(1.27mm) Dual Row Header, SMT Type


Specifications:

- Current rating: 1A
- Contact resistance: 20mΩ Max.
- Dielectric withstanding voltage: 300V AC/minute
- Ambient temperature range: -40 °C ~ 105 °C
- Max. process Temp.: 230 °C for 30 ~ 60 sec.
(260 °C for 10 seconds)

12703WMS-SMT-N Series

Dual Row, SMT Type

- 4 ~ 100 circuits available
- Material: Polyester, UL 94V-0 nylon
- Gold flash phosphor bronze
- .016"(0.4mm) right angle square wire pins



Dimensional Information (mm)

Dim. A	Dim. B
$1.27 \times (N / 2 - 1)$	$1.27 \times N / 2$


& N = Number of contact, 4 ~ 100

Recommended P.C.B hole pattern

12703HFS-SMT-N Series

Dual Row, SMT Type

- 10 ~ 100 circuits available
- Material: UL 94V-0 Nylon 6T
- Gold flash phosphor bronze



Dimensional Information (mm)

Dim. A	Dim. B
$1.27 \times (N / 2 - 1)$	$1.27 \times N / 2 + 0.35$

& N = Number of contact, 10 ~ 100

Recommended P.C.B hole pattern