




**TDC Power Products Co.,Ltd**  
**Cheng Yen Electronic Co.,Ltd**

**SA8E-280-0220WP**

**INPUT VOLTAGE : 220~240VAC**  
**OUTPUT VOLTAGE : 28VDC**

**SWITCHING POWER SUPPLY SPECIFICATION REV:A**

**Drawing:**



**ELECTRONICAL SPECIFICATION**

INPUT VOLTAGE : 220~240 Vac    INPUT RANGE VOLTAGE 200~264 Vac  
 INPUT FREQUENCY : 50 Hz    INPUT RANGE FREQUENCY 47~53 Hz  
 INPUT CURRENT : 0.06 Amp. rms. at 240 Vac  
 INRUSH CURRENT : 30 Amp. peak at 240 Vac  
 Tested At Max. load 25°C , Cold start

OUTPUT VOLTAGE : 28 V  
 REGULATION : ±5 %  
 MIN. LOAD CURRENT : 0 A  
 MAX. LOAD CURRENT : 0.22 A  
 POWER FACTOR ≥ 0.85 at 230 Vac /50 Hz Full Load .Meets IEC61000-3-2 Harmonic Class C  
 RIPPLE AND NOISE : 1.3 Vp-p Max. At 240 Vac, 50 Hz, Max. load 25°C  
 NOISE TEST BANDWIDTH : 20 MHz

Each output bypassed by a 10uF electrolytic capacitor parallel with a 0.1uF ceramic capacitor to GND.

LINE REGULATION : INPUT = 220 ~ 240 Vac,output loaded at Max. load.  
 REGULATION = ±5 %

TOTAL OUTPUT : 6.1 W  
 POWER EFFICIENCY : 75% Min. at 220~240 Vac 50 Hz, Max. load.  
 OVER CURRENT PROTECTION , SHORT CIRCUIT PROTECTION  
 TOTAL POWER PROTECTION : 18 W  
 OVER VOLTAGE PROTECTION : 36 Vdc Max.

**MECHANICAL SPECIFICATION**


Dimensions : 83.1(L) \* 54.1 (W) \* 33.2(H)mm (Tolerance as drawing)  
 Weight : 180 g Max.  
 Operating Temperature : 0°C To 40°C  
 Storage Temperature : -15°C To 50°C  
 Relative Temperature : 40°C ± 2°C  
 MTBF: 50,000 hrs to MIL-HDBK-217F    Warranty: 2 years

**Input Cable : DIRECT PLUG-IN**

**Output Cable :** 2Pin Φ2.35 waterproof  
 Female socket BK

**LABEL:**

SIZE:34.6\*44.6mm



**STANDARD**

Safety:EN61347-1,EN61347-2-13.    EMC:EN61547,EN55015,EN61000-3-2,EN61000-3-

**RELATIVE HUMIDITY** 85% RH. Non-condensing

**INNER BOX:**

**Material: WEB**

**BOX: 110\*60\*90mm**

**CARTON: 460\*320\*290mm**



**Material:K=A No Nail**

**Q'TY: 60 PCS**

**N.W.: 10.8 KGS**

**G.W.: 13.2 KGS**

**MEAS: 1.5 CUFT**



**photo**

