


606-2

Female Header 1.27mm Pitch Low Profile SMT Type For square pin

Technical Data :

Insulator Material: High Temperature Thermoplastic, UL 94V-0
 Contact : stamped and formed, Phosphor Bronze
 Plating: Au or Sn over Nickel
 Current Rating : 1 Amp
 Contact resistance: 20 milliohms Max.
 Insulator resistance : 500 Megohms min.
 Dielectric withstanding : AC 500V for 1 Minute.
 Operating Temperature: -40°C to +105°C.
 Max. processing Temp: 230°C for 30-60 seconds.
 260°C for 10 seconds.
 Mates with : Pitch 1.27mm, □0.40mm male header




RoHS Compliant

Length of the Cap Option	
06-08 Pin	L=3.0mm
10-100 Pin	L=6.35mm

Recommended P.C.Board Hole Layout

How to order



Number of contact	Code
Double Row Max. 80	04-80

Plating option	Code
Gold plated	10
Tin Plated	50
Selective gold flash plated	60

Pick & Place Pad	Code
W/ Cap	1
W/O Cap	2

Location Peg Option	Code	Note
W/ Location Peg	10	6Pin Min
W/O Location Peg	00	

Packing Option	Code
Tube	1
Tape & Reel	2

W.E.