

.079" (2.0mm) Crimp Terminal Housing


Specifications:

- Current rating: 3A AC, DC
- Voltage rating: 250V AC, DC
- Contact resistance: 20mΩ Max.

- Insulation resistance: 1000MΩ Max.
- Dielectric withstanding voltage: 800V AC/minute
- Temperature range: -25 °C ~ 85 °C (Including temperature rise)


20006T Series Crimp Terminal

- Material: Phosphor bronze
- Finished: Tin-plated
- Used in 20006H-N housing
- Wire range: AWG #24 ~ #30
- Thickness: 0.2mm



20006H-N Series Crimp Terminal Housing

- 2 - 16 circuits available
- Material: UL 94V-0 nylon 66
- Standard color: White
- Accepts 20006T terminal
- Mates with 20006W-N headers



Ordering Information

Part No.	Feature
20006H-N	Without side pole
20006H-P-N	With side pole

&& xx = 02 - 16

Dimensional Information - in (mm)

Circuits	Dim. A	Dim. B	Dim. C	Circuits	Dim. A	Dim. B	Dim. C
2	0.079 (2.0)	0.181 (4.6)	0.091 (2.3)	10	0.709 (18.0)	0.811 (20.6)	0.484 (12.3)
3	0.157 (4.0)	0.260 (6.6)	0.091 (2.3)	11	0.787 (20.0)	0.890 (22.6)	0.638 (16.2)
4	0.236 (6.0)	0.339 (8.6)	0.169 (4.3)	12	0.866 (22.0)	0.969 (24.6)	0.638 (16.2)
5	0.315 (8.0)	0.417 (10.6)	0.169 (4.3)	13	0.945 (24.0)	1.047 (26.6)	0.638 (16.2)
6	0.394 (10.0)	0.496 (12.6)	0.327 (8.3)	14	1.024 (26.0)	1.126 (28.6)	0.638 (16.2)
7	0.472 (12.0)	0.575 (14.6)	0.406 (10.3)	15	1.102 (28.0)	1.205 (30.6)	0.638 (16.2)
8	0.551 (14.0)	0.654 (16.6)	0.484 (12.3)	16	1.181 (30.0)	1.283 (32.6)	0.638 (16.2)
9	0.630 (16.0)	0.732 (18.6)	0.484 (12.3)				