

.100"(2.54mm) Dual Row Pin Header, SMT


Specifications:

- Current rating: 3A
- Contact resistance: 20mΩ Max.
- Dielectric withstanding voltage: 600V AC/minute
- Ambient temperature range: -40 °C ~ 105 °C

25410WMR-SMT-N Series

Dual Row Header, SMT

- 4 ~ 80 circuits available
- Plastic material: Nylon 6T
- Pin material: Gold-flash Copper Alloy
- .025"(0.64mm) square pin
- Pin length: Custom length available



PCB Layout: Component side

Dimensional Information - in (mm)

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
4	0.1 (2.54)	0.2 (5.08)	30	1.4 (35.56)	1.5 (38.10)	56	2.7 (68.58)	2.8 (71.12)
6	0.2 (5.08)	0.3 (7.62)	32	1.5 (38.10)	1.6 (40.64)	58	2.8 (71.12)	2.9 (73.66)
8	0.3 (7.62)	0.4 (10.16)	34	1.6 (40.64)	1.7 (43.18)	60	2.9 (73.66)	3.0 (76.20)
10	0.4 (10.16)	0.5 (12.70)	36	1.7 (43.18)	1.8 (45.72)	62	3.0 (76.20)	3.1 (78.74)
12	0.5 (12.70)	0.6 (15.24)	38	1.8 (45.72)	1.9 (48.26)	64	3.1 (78.74)	3.2 (81.28)
14	0.6 (15.24)	0.7 (17.78)	40	1.9 (48.26)	2.0 (50.80)	66	3.2 (81.28)	3.3 (83.82)
16	0.7 (17.78)	0.8 (20.32)	42	2.0 (50.80)	2.1 (53.34)	68	3.3 (83.82)	3.4 (86.36)
18	0.8 (20.32)	0.9 (22.86)	44	2.1 (53.34)	2.2 (55.88)	70	3.4 (86.36)	3.5 (88.90)
20	0.9 (22.86)	1.0 (25.40)	46	2.2 (55.88)	2.3 (58.42)	72	3.5 (88.90)	3.6 (91.44)
22	1.0 (25.40)	1.1 (27.94)	48	2.3 (58.42)	2.4 (60.96)	74	3.6 (91.44)	3.7 (93.98)
24	1.1 (27.94)	1.2 (30.48)	50	2.4 (60.96)	2.5 (63.50)	76	3.7 (93.98)	3.8 (96.52)
26	1.2 (30.48)	1.3 (33.02)	52	2.5 (63.50)	2.6 (66.04)	78	3.8 (96.52)	3.9 (99.06)
28	1.3 (33.02)	1.4 (35.56)	54	2.6 (66.04)	2.7 (68.58)	80	3.9 (99.06)	4.0 (101.60)