


.163"(4.14mm) Wire to Wire Connectors

41401TM SERIES Male Crimp Terminal

41401TF SERIES Female Crimp Terminal


inches
mm



Ordering Information

Part No.	Material
4140 ITM	Brass
4140 ITMP	Phosphor bronze

- Finished: Tin-plated
- Used in 41401H housing
- Wire range: #18 ~ #24 AWG
- Thickness: 0.2mm



Ordering Information

Part No.	Material
4140 ITF	Brass
4140 ITFP	Phosphor bronze

- Current rating: 5A AC, DC
- Voltage rating: 300V AC, DC
- Dielectric withstanding voltage: 1500V AC/minute
- Ambient temperature range: -25°C ~ 90°C

41401H SERIES Crimp Terminal Housing

inches
mm

- Integrally molded polarization
- UL 94V-2 nylon 66
- Accepts _____ terminals

- 1, 2, 3, 4, 6, 9, 12, 15 circuits available
- Color: Nature
- Positive locking
- Insulation resistance: 1000MΩ Min.

Circuits	Dimensional Information	
	Plug	Receptacle
1	<p>41401HF-01</p>	<p>41401HM-01</p>
2	<p>41401HF-02 (W/O Mtg. Ears) 41401HFE-02</p>	<p>41401HM-02</p>
3	<p>41401HF-03 (W/O Mtg. Ears) 41401HFE-03</p>	<p>41401HM-03</p>