

PCB LAYOUT
TOLERANCES: ±0.05

PART LIST				
NO.	COMPONENT	QUANTITY	MATERIAL	FINISH
1	HOUSING	1 PCS	THERMOPLASTIC, COLOR IN BLACK, UL94V-0 RATED	-
2	CONTACT	5 PCS	HIGH PERFORMANCE COPPER ALLOY	GOLD OVER NICKEL IN CONTACT AREA TIN-LEAD OVER NICKEL IN SOLDER TAIL
3	SHELL	1 PCS	HIGH PERFORMANCE COPPER ALLOY	TIN-LEAD OVER NICKEL
4	MYLAR	-	-	-

NOTES:

1.COPLANARITY:0.10MAX



Part number : YMUVG 3 0 1 1 3 -X X

T T T
a b c

a:CONTACT PLATING
1:FLASH GOLD
3:GOLD 30u"

b:MYLAR
1:YES
2:NO

c:SHELL PLATING
B:TIN-LEAD(鍍錫)
C:TIN-LEAD(鍍錫)



Remove burrs, Break sharp edges 0.4 R. max.
Stamp part no. in area indicated by "x"
Unless otherwise specified
Angle: ±1°

XX.X = ±0.20 .X" = ±
XX.XX = ±0.10 .XX" = ±
XX.XXX = ±0.05 .XXX" = ±

01	設計發行	CHEN 05/05/2004	料號	YMUVG30113-XX
TITLE		Mini-B 5p socket		
SHEET	1/1	App.	Chk.	Drf.
SCALE	1 : 1	CHEN 05/09/2004	CHEN 05/07/2004	CHEN 05/05/2004
譽盛精密工業股份有限公司				